

Technical drawing of a ball joint showing dimensions A, B, C, D, E, and G. The drawing includes a side view and a cross-sectional view. The side view shows the overall width (A), the width of the ball (D), the width of the housing (G), and the height of the housing (C). The cross-sectional view shows the height of the housing (B) and the height of the ball (E).

The image contains two technical drawings of a tapered roller bearing. The left drawing is a cross-section showing the internal structure with dimensions: A (outer diameter), F (inner diameter), D (width), and B (inner ring width). The right drawing is an end view showing the tapered rollers with dimensions: C (outer diameter), E (inner diameter), and G (width).

Fig.3

規格 (Type)	尺寸(Unit : mm)									圖形	磁芯參數				單重 (g/prs)	Al-value (nH/N ²)							
	A	B	C	D	D1	D2	E	F	G		C1 (mm ⁻¹)	Le (mm)	Ae (mm ²)	Ve (mm ³)		GP4	GP44	GP47	GP90	GP95	GP95B	GP96	
CV25-16.9	25.0±0.4	8.45±0.15	16.8±0.3	11.5±0.3			20.4±0.4	5.75±0.15	14.8min	Fig.1	0.487	42.38	87.2	3696	22.1	4100	4300	4300	3700	5100	5100	5100	
CV27-14.5	27.0±0.4	7.25±0.15	18.0±0.3	4.25±0.15			22.0±0.4/-0.3	11.0±0.2	17.1±0.4	Fig.2	0.43	41.87	96.3	4032	21.8	4600	4700	4800	4200	5600	5600	5600	
CV3014	30.0±0.5	7.0±0.15	20.3±0.3	13.3±0.2			25.4±0.5	4.2±0.15	18.7±0.5	Fig.1	0.374	40	107	4280	26				5000				
CV3318	33.2±0.4	9.0±0.15	21.7±0.3	6.2±0.15			26.8±0.4	13.4±0.2	19.1±0.6	Fig.2	0.409	52.3	127.8	6682.26	18.8				4700				
CV35-14.8	35.2±0.5	7.4±0.15	21.7±0.35	4.6±0.15			28.8±0.6/-0.4	13.4±0.25	21.3±0.6	Fig.2	0.378	46.6	123.33	5747.18	17.4			5800					
CV37-11.6	37.0±0.6	5.8±0.15	27.4±0.5	15.4±0.3			30.75±0.6	2.9+0.3/-0.05	20.0+0.6/-0.35	Fig.1	0.264	40.53	153.68	6228.85	36							8800	
CV37-12.5	37.3±0.5	6.25±0.15	27.5±0.4		31.0±0.5	21.0+0.6/-0.4	15.4+0.25/-0.3	3.05±0.15		Fig.3	0.262	41.37	157.95	6535	39.4				6600				
CV40-17.6	39.8+0.5/-0.4	8.8±0.15	28.3±0.4	5.2±0.15			33.2±0.5/-0.4	16.0±0.25	21.2+0.7/-0.4	Fig.1	0.284	52.85	186.16	9838.6	56.9			7300					